

揚聲器製品規格書

SPEAKER SPECIFICATION

Neodymium tweeter HT-NH75-1



Model : HT-NH75-1

specifications				mounting and shipping information	
Throat Diameter	36mm (1.4 in)	Frequency Range	0.8K-20kHz	Four M6 holes 90° on 100mm (4in) diameter	
Impedance	8Ω	Recommended crossover	1.2kHz	Overall Diameter	130mm (5.2 in)
D.C.Resistance	6.2Ω	Voice Coil Diameter	75mm (3in)	Depth	65mm (2.6 in)
Nominal Power	110w	Winding Material	Aluminium	Net Weight (1 unit)	2.6kg (5.8 lb)
Maximum Power	220w	Inductance	0.14mH	Shipping Weight (10units)	11.0kg (24.5 lb)
Sensitivity(1W/1m)	108 dB	Diaphragm Material	Composite	Shipping Box (10 units)	300*160*180mm (11.8*6.3*7.1in)
		Polyimide/Titanium			
		Magnet Material	Neodymium Ring		

Also available in 16Ω , data upon request

1 Driver mounted on B&C ME45 horn.

2 2 hours test made with continuous pink noise signal (6dB crest factor) within the specified range. Power calculated on rated minimum impedance .

3 Power on Continuous Program is defined as 3dB greater then the Nominal rating.

4 Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance. Average SPL from 1000 to 18000 Hz.

5 12 dB/oct. Or higher slope high-pass filter.

SPL vs Freq



Impedance vs Freq

